

# **Add more** Do more

With John Deere 6D Tractor attachments



## Canopy

Get comfort and protection from the sun's harmful rays.

**AR201256** Canopy for Roll-Guard, Open Station Only



## Quik-Coupler – Category 2

Adds more convenience when attaching or detaching implements to the rear of your tractor.

**TY16042**



## MFWD Front Fenders

Protects your operator station from unwanted debris.

**SJ291766**



## Work Light Kits

Work long past sunset and increase productivity with powerful illumination.

**SJ291699** Fender Mounted (LH and RH), Front Facing, Open Station Only

**LVB25720** Aux Work Light (2 Lights), Cab Tractors Only



## Rear Wheel Weight

Provides additional ballast and traction.

**APY10029** 4 – 120-lb. wheel weights

**L28228** 120-lb. wheel weight

## BUY NOW, PAY LATER

When you put it on your multi-use account.  
Ask us for details!\*



## Hydraulic Kits

Boost performance with additional hydraulic attachments.

**BSJ10049** Triple Deluxe SCV Kit, Converts from Dual Standard to Triple Deluxe SCV

*See your dealer for a complete offering of mid and rear SCV kits.*

*Talk to us today about how attachments can **Add More** to your tractor experience.*



# Protect your equipment With John Deere filters

6105D / 6115D / 6130D / 6140D I4 TRACTORS

Engine Air Filter



Cab Air Filters – 2



5



Engine Oil Filter



Hydraulic Filter



Fuel Filters

## 1 Engine Air Filter

Highly efficient filters reduce engine wear by removing rust, dirt and other pollutants from intake air. Replace primary element every 1,200 hours or annually as required by conditions.

SU20768 Primary  
RE253519 Secondary

## 2 Cab Air Filters – 2

Keeps inside cab air fresh and flowing, and dust and pesticide vapors outside. Clean every 600 hours or annually as required by conditions.

RE198488 Fresh Air  
RE195491 Recirculation Air

## 3 Hydraulic Filter

Designed to protect hydraulic systems from component wear and surge flow. Replace every 500 hours.

SJ11792

## 4 Fuel Filters

Designed to trap and repel water—fuel's number one enemy. Prevents rust and microbial growth that can damage fuel and lead to poor fuel economy. Replace every 500 hours.

RE541922 Primary  
RE544394 Final

## 5 Engine Oil Filter

Superior protection with rubber gaskets that resist decomposition. Replace every 300 hours. If using Plus-50™ II, interval can be increased to 500 hours.

RE504836

*Don't forget the recommended John Deere fluids for your machine!*

